

Standard features

- Available with manual or electric winch;
- 3 position arrow (4'13/4" lenght 1.26m);
- The arrow turns easily with the maximum load;
- Continuous 360° manual rotation;
- 3/16" (5mm) cable with a length of 25' (7.62m);
- The crane is easily removed from its base;
- The arrow retracts easily for transportation;
- 4' 83/4" (1.44m) storage height;
- Very lightweight, from 130 lbs. to 150 lbs.;
- Optional removable control box with up to a 10' (3m) range (used with electric winch only);



 The vehicle's electric system must have a minimum of 12 volts. 80 A/hr, a battery with a capacity of 450 cold starts and a 50 A alternator (only for the electric winch);

Spécifications

- Lifting capacity (at all points): 1,000 lbs. (454kgs);
- Turning radius: 360°;
- Weight (with manual winch): 130 lbs. (59 kgs);
- Weight (with electric winch): 140 lbs. (63 kgs);
- Weight (with electric winch and control box): 150 lbs. (68 kgs);
- Required mounting surface (bottom plate is 12" X 12" (300 X 300 mm);
- Model for bolt holes: 9 ½" X 9 ½" (241.3 X 241.3 mm).

Équipments TWIN Inc. guarantees each new TWIN-LIFT product against defects in materials and workmanship for a period of one year from the date of purchase. The obligation under this warranty, whether statutory or otherwise, is limited to replacement or repair at our factory of one of the part that, after our inspection, seems defective in material and/or workmanship. Equipment TWIN Inc. makes no warranty on accessory components that are prone to guarantees offered by their respective manufacturers.

The TWIN-LIFT crane was not designed neither to raise nor to move people.

A copy of the warranty statement is packed with each product.

Équipements TWIN Inc. 10401 boul. Parkway Anjou (Québec) H1J 1R4

MONTRÉAL

Tel: (514) 353-1190 Telec:(514) 353-1119

TF: (877) 300-8946

info@egtwin.ca

